

FLAMED WOOD

Product Description:

Flamed Wood represents charred wood without being actually burned. The burned optic is gained by the special embossing process of multiple veneer layers. No unpleasant burnt smell, no dark stains, no crumbling and a closed surface, which does not need to be fixed afterwards.

Composition:

Flamed Wood is an embossed panel with special developed veneer and melamine resins with a black MDF core (9mm).or particle board (20mm).

Fields of application:

Only for interior: wall cladding, interior fitout, shop and Shop and fair construction. Doors.

Technical Data:

First given measurement specifies the direction of embossment:

Invoiced size (mm): 2450 x 1050 / 3135 x 1270
Delivered size (mm): 2450 x 1050 / 3145 x 1280

Repeating pattern: No repeating pattern

Available thicknesses: 9mm, 20mm
Coreboard: black MDF, Particle board
Surface: raw, unlacquered

Density: ca. 1026 kg/m³
Weight: ca. 9.5 kg/m² (9mm)
ca. 16 kg/m² (20mm)

Embossment: one-side
Deepness of structure: max. 1.5 mm

Tolerancen:

Straightness: 3.0 mm pro Metre
Size accuracy: +/- 1.0 mm pro Metre
Thickness allowance: +/- 0.3 mm
Exactitude of profile: +/- 1.5 mm



Black
Fineline veneer

Explanatory notes:

The given details in this data sheet are our field-tested experience. They could not consider every parameter, use case or application and they are therefore without commitment. These data does not represent guarantee of condition in the legal sense or a assurance of the characteristics. No legal claims could be derived by using the information given in these data sheets or by our free of charge technical consultants. Images are for illustration purposes only. Wood is a natural product, deviations in color and texture can occur. Please visit our website for an impression of the color range, which can be expected.