

ANTIKWOOD

Product Description:

Antikwood creates the look of old, rustic wood by combining real wood veneers with a surface that appears slightly brushed. The structure is rather straight-lined and even.

Composition:

Antikwood is an embossed panel with special developed compositions of veneers with solid wood / a plywood core.

Fields of application:

Only for interior: wall cladding, interior fitout, shop and Shop and fair construction. Doors.

Technical Data:

First given measurement specifies the direction of embossment:

Invoiced size (mm): 3135 x 1270 / 1270 x 3135
Delivered size (mm): 3145 x 1280 / 1280 x 3145

Repeating pattern: No repeating pattern

Available thicknesses: 5 mm / 18.5 mm
Coreboard: Multi layer construction /
Plywood
Surface: raw, unlacquered

Density: ca. 850 kg/m³
Weight: ca. 4 kg/m² (5 mm)
ca. 16 kg/m² (18.5 mm)

Embossment: one-side
Deepness of structure: max. 2.6 mm

Tolerances:

Straightness: 3.0 mm per Metre
Size accuracy: +/- 1.0 mm per Metre
Thickness allowance: +/- 0.5 mm
Exactitude of profile: +/- 1.5 mm



Knob Oak
Real wood veneer

Explanatory notes:

The given details in this data sheet are our field-tested experience. They could not consider every parameter, use case or application and they are therefore without commitment. These data does not represent guarantee of condition in the legal sense or a assurance of the characteristics. No legal claims could be derived by using the information given in these data sheets or by our free of charge technical consultants. Images are for illustration purposes only. Wood is a natural product, deviations in color and texture can occur. Please visit our website for an impression of the color range, which can be expected.